

Подключается с помощью кабеля для непосредственной установки на группы МК с 3-ходовым клапаном (Поколение 8, Поколение 8+), время работы 140 сек. 90°, крутящий момент 6 Нм, с ручным аварийным режимом и доступным для проверки индикатором положения.

- В комплекте монтажный набор.



Описание	Actuator 230 V, grey
Артикул	M66341
GTIN	04016715009319
Модель	<u>Электрические приводы</u>
Комплектация	230 V

Классификация основные сведения

Тип продуктовой группы	Spare parts for fittings
Класс продуктовой группы	Electric servomotor
Название продукта	STELLMOTOR 140S 6 NM 230V GRAU 2M KABEL
Брэнд	FLAMCO
Тип продукта	
Артикул	M66341
GTIN	04016715009319

Дополнительные сведения

Suitable for valve	Да
Suitable for air accessory	Нет
Control signal	3-point
Communication bus	Другое
Communications protocol	Отсутствует
Energy consumption in operation	2.5 Watt
Regulation type on/off	Да
Regulation type modulating	Нет
Regulation type splitrage	Нет
Connection cable length	2 Metre
Transmission	With cogwheels
Connection to stop valve	Brand-dependent
With top flange direct mount according to ISO 5211	Нет
Return at zero supply voltage	Нет
Deactivated when closed	Да
Type of safety function	Electronic
Principle of operation safety function	Другое
Automatic stroke recognition	Нет
Adjustable position feedback signal	Нет
Auxiliary contacts	Нет
Position reporting system	Отсутствует
Auxiliary contacts optional	Нет
End contacts	2
Adjustable operating range	Нет
With mechanical setting indicator	Да
Suitable for manual operation	Да
Operating time	140 Second
Torque	6 Newtonmetre
Potential free switch contact	Нет
Self-adjusting travel length	Нет
Max. angle of rotation	90 Degrees
With safety function	Нет
Степень защиты (NEMA)	Другое
Max. electric power input	2 Voltampere
Высота	93 Millimetre
Ширина	80 Millimetre
Глубина	75 Millimetre
Взрывозащищенный	Да
Housing material	Пластик